

NVS0104DH-4K

Ultra-HD Network Video Decoder



Features :

- Designed for standalone operator viewers
- H.264/MPEG-4 video decoding
- 4ch@12Mp/4ch@4K/16ch@1080P/36ch@720P/64ch@D1 decoding ability
- Support multiple resolution decoding: up to 8Mp and 12Mp network video
- 1ch HDMI/VGA output, HDMI support Ultra HD 4K output
- Support 1/4/9/16/25/36/64 display split
- Support audio, alarm, bi-directional talk, RS485
- Local GUI support mouse operation directly



Technical Specification

System

Processor	Intel x86 processor
Operating System	LINUX

Performance

Video Format	H.264/MPEG4/ MJPEG
Audio Format	PCM/G.711
Decoding Resolution	12MP/8MP/5MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF
Video Output	HDMI/VGA
Display Resolution	3840×2160/1920×1080/1280×1024/1280×720/1024×768
Audio Output	HDMI
Communication Interface	1 RJ45 network port (10M/100M/1000M); 1 RS232(DB9); RS485
Bi-directional Talk	1 channel, RCA in / RCA out (2Vrms, 10K ohms)
Alarm Input	4ch
Alarm Output	4ch relay out (30VDC 1A, 125VAC, 0.5A)

Others

Power Supply	DC12V, 3.3A
Power Consumption	≤20W
Working Temperature	-10C~+55C
Working Humidity	10%~95%, 86Kpa~106Kpa
Unit Dimension	1U, 440mm×300mm×42.1mm(W*D*H)
Weight	3.5Kg